

## Powerful entry-level business media phones for today's cubicle workers handling a low to moderate volume of calls delivering crystal clear communications

The Polycom® VWX® 300/310 is an expandable business media phone that delivers crystal clear communications, enhanced collaboration and personal productivity.



### **Simplicity and ease-of-use**

The VWX 300/310 phone brings high-quality, cost effective solutions to any environment through advanced UC features. The intuitive user interface of the VWX 300/310 makes usability and navigation easy and requires minimal training.

### **Customizable and expandable**

The VWX 300/310 phone provides personalized information at a glance, through built-in web applications and custom backgrounds. The VWX 300/310 phone also comes ready for future expansion modules as your users' needs and business grows.

### **Unsurpassed voice quality and clarity**

The VWX 300/310 delivers breakthrough Polycom® HD Voice™ quality for life-like conversations while minimizing fatigue making calls more efficient and productive.

### **Market-leading open standards interoperability**

Designed for enhanced interoperability, the VWX 300/310 leverages and complements the other existing IT investments in your business. With the broadest call server interoperability in the industry, the Polycom VWX 300/310 entry level business media phone can become the flexible and future-proof foundation for any organization's unified communications strategy.

### **Maximize productivity**

Give your front line workers the best experience with this high quality two-line business media phone.

### **Benefits**

- Improve productivity for cubicle workers and call center operators through an intuitive easy to use user interface
- Make more efficient and productive calls with the unparalleled voice clarity of Polycom® HD Voice™
- Leverage previous IT infrastructure investments—deploy VWX 300/310 business media phones on your existing network without needing to upgrade your call control platform

# Polycom® VVX® 300/310 Series

## USER INTERFACE FEATURES

- Backlit 8-level Grayscale graphical LCD (208 x 104) resolution
- Voicemail support
- Adjustable base height
- Unicode UTF-8 character support. Multilingual user interface including Chinese, Danish, Dutch, English (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish, and Swedish

## AUDIO FEATURES

- Polycom HD Voice technology delivers life-like voice quality for each audio pathhandset, the hands-free speakerphone, and the optional headset
- Polycom® Acoustic Clarity™ technology providing full-duplex conversations, acoustic echo cancellation and background noise suppression -- Type 1 compliant (IEEE 1329 full duplex)
- Frequency response – 150 Hz – 7 kHz for handset, optional headset and handsfree speakerphone modes
- Individual volume settings with visual feedback for each audio path
- DTMF tone generation (RFC 2833 and in-band)

## HEADSET AND HEARING AID COMPATIBILITY

- Dedicated RJ-9 headset port
- Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
- Compliant with ADA Section 508 Subpart B 1194.23 (all)
- Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- Compatible with commercially-available TTY adapter equipment

## CALL HANDLING FEATURES

- 2 lines (programmable line keys)
- Busy Lamp Field (BLF)
- Call timer and call waiting
- Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- Local three-way audio conferencing
- One-touch speed dial, redial
- Do not disturb function

## POWER

- External Universal AC Adapter 48VDC; 12W

## APPROVALS

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- VCCI Class B
- EN55024
- EN61000-3-2; EN61000-3-3
- NZ Telepermit
- Korea KC<sup>3</sup>
- UAE TRA
- Russia GOST-R<sup>3</sup>
- Brazil ANATEL<sup>3</sup>
- Australia A & C Tick

## SAFETY

- UL 60950-1
- CE Mark
- CAN/CSA C22.2 No 60950-1
- EN 60950-1
- IEC 60950-1
- AS/NZS 60950-1
- ICASA (add)
- CITC (add)

## OPERATING CONDITIONS

- Temperature: 0 – 40°C (32 – 104°F)
- Relative Humidity: 5% to 95%, noncondensing

## STORAGE TEMPERATURE

- -40 – +70°C (-40 – +160°F)

## POLYCOM VVX 300/310 COMES WITH:

- VVX 300/310 console
- Handset with handset cord
- Network (LAN) Cable - CAT-5E

## SIZE

- 19 x 15 x 18 cm (7.5 x 6 x 7 in) (W x H x D)

## PART NUMBERS

- 2200-46135-025 – VVX 400 WW PoE
- 2200-46161-025 – VVX 410 WW PoE

## WEIGHT

- 2.0 lbs (0.9 kg)

## UNIT BOX DIMENSIONS

- 12 x 8.25 x 4.25 in
- 3.1 lbs (1.4 kg)

## COUNTRY OF ORIGIN

- China

## WARRANTY

- One (1) year