

Polycom® VVX® 310

Gigabit desk phone

6-line desktop system
with LCD display



The phone has 6 lines for low to moderate call volume and HD voice¹ for superior sound quality. Patented Acoustic technology provides echo-free and crystal-clear conversations.

The Presence feature of this phone allows the user to monitor the in-use status of up to 4 other users. The intuitive user interface makes usability and navigation easy and requires minimal training.

Its two-port Gigabit Ethernet switch allows a single drop to the desktop for high-speed connection to both phone and computer.

¹HD Voice is available for RingCentral customers in selecting plans.

Features and Specifications

Lines

- 6 lines for calls or use up to 4 for presence monitoring

Display

- Backlit 8-level grayscale graphical LCD 208 x 104 resolution

Headset and hearing aid compatibility

- Dedicated RJ-9 headset port
- Hearing aid compatibility ITU-T P.370 and TIA 504A standards
- Compliant with ADA Section 508 Subpart B 1194.23 (all)
- Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- Compatible with commercially-available TTY adapter equipment

Audio Features

- Polycom HD Voice technology delivers life-like voice quality for each audio path - handset, the hands-free speakerphone, and the optional headset²
- Polycom® Acoustic Clarity™ technology providing full-duplex conversations, acoustic echo cancellation and background noise suppression - Type 1 compliant (IEEE 1329 full duplex)
- Frequency response – 150 Hz – 7 kHz for handset, optional headset and hands-free speakerphone modes
- Codecs: G.711 (A-law and μ -law), G.729AB, G.722, G.722.1, iLBC
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise generation
- DTMF tone generation (RFC 2833 and in-band)
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment

Call Handling Features

- 6 lines (programmable line keys)
- Busy Lamp Field (BLF)
- Distinctive incoming call treatment/call waiting
- Call timer and call waiting
- Call transfer, hold, divert (forw3ard), pickup
- Called, calling, connected party information
- Local three-way audio conferencing
- One-touch speed dial, redial
- Remote missed call notification
- Do not disturb function
- Electronic hook switch capable
- Local configurable digit map/dial plan

Other Features

- Adjustable base height

Protocol Support

- IETF SIP (RFC 3261 and companion RFCs)

Network and Provisioning

- SIP Protocol Support
- SDP
- IETF SIP (RFC 3261 and companion RFCs)
- Two-port Gigabit Ethernet switch
 - » 10/100/1000Base-TX across LAN and PC ports
 - » Conforms to IEEE802.3-2005 (Clause 40) for Physical Media Attachment
 - » Conforms to IEEE802.3-2002 (Clause 28) for link Partner Auto-Negotiation
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronization using SNTP

- FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments
- Provisioning and call server redundancy supported
- QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP
- VLAN - CDP, DHCP VLAN discovery, LLDP-MED for VLAN discovery
 - » Network Address Translation (NAT) support for static configuration and “Keep-Alive” SIP signaling
- RTCP and RTP support
- Event logging
- Syslog
- Hardware diagnostics
- Status and statistics reporting
- IPv4
- TCP
- UDP
- DNS-SRV

Power

- Built-in auto sensing IEEE 802.3 at Power over Ethernet (Class 2)
- External Universal AC Adaptor, 48VDC; 12W

Approvals

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- VCCI Class B
- EN55024
- EN61000-3-2; EN61000-3-3
- NZ Telepermit
- UAE TRA
- Australia A & C Tick

² To enjoy all the benefits of Polycom HD Voice when using the phone in the headset mode, you must use a wideband headset.

Features and Specifications continued

Safety

- UL 60950-1
- CE Mark
- CAN/CSA-C22.2 No. 60950-1
- EN 60950-1
- IEC 60950-1
- AS/NZS 60950-1
- ICASA (add)
- CITC (add)

Operating Conditions

- Temperature: (+32 to 104°F (0 to 40°C)
- Relative Humidity: 5% to 95%, noncondensing

Storage Temperature

- -40 to +160°F (-40 to +70°C)

Package Contents

- VVX 310 console
- Handset with handset cord
- Network (LAN) cable – CAT-5E
- User guide
- Quick Tips reference card
- Ferrite clamp
- Power supply

Size

- 7.5 x 6 x 7 in (19 x 15 x 18 cm) (WxHxD)

Box Dimensions/Weight

- Unit weight: 2.0 lbs (0.9 kg)
- 12 x 8.25 x 4.25 in
- 3.1 lbs (1.4 kg)

Country of Origin

- China