

# Polycom<sup>®</sup> VVX<sup>®</sup> 410

Gigabit desk phone

12-line desktop system  
with color LCD display



The phone has 12 lines for moderate to high call volume and HD voice<sup>1</sup> for superior sound quality. Patented Acoustic technology provides echo-free and crystal-clear conversations.

The Presence feature of this phone allows the user to monitor the in-use status of up to 10/50<sup>2</sup> other users. The intuitive user interface makes usability and navigation easy and requires minimal training.

Its two-port Gigabit Ethernet switch allows a single drop to the desktop for high-speed connection to both phone and computer.

<sup>1</sup> HD Voice is available for RingCentral customers in selecting plans.

<sup>2</sup> Up to 50 users with an extension module

## Polycom VVX 410 available with an extension module

Turn your business phone into a high performance attendant console with this optimal solution for telephone attendants and other “power users” who manage multiple simultaneous telephone calls or monitor presence on a daily basis.

- Show presence for up to 50<sup>3</sup> other users with an expansion module using innovative multi-page display
- Augments host phone user interface
- Creates a high performance productivity enhancing solution with host phone
- Easy installation to host phone
- Programmable, illuminated bi-color LED keys
- High resolution graphical color display



VVX 410 + 1 Expansion Module

## Features and Specifications

### Lines

- 12 lines for calls or use up to 10/50<sup>4</sup> for presence monitoring

### Display

- 3.5 in TFT LCD display at QVGA (320 x 240 pixel) resolution, 4:3 aspect ratio

### Headset and hearing aid compatibility

- Dedicated RJ-9 headset port
- Hearing aid compatibility ITU-T P.370 and TIA 504A standards
- Compliant with ADA Section 508 Subpart B 1194.23 (all)

- Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- Compatible with commercially-available TTY adapter equipment

### Audio Features

- Polycom HD Voice technology delivers life-like voice quality for each audio path - handset, the hands-free speakerphone, and the optional headset<sup>5</sup>
- Polycom® Acoustic Clarity™ technology providing full-duplex conversations, acoustic echo cancellation and background noise suppression - Type 1 compliant (IEEE 1329 full duplex)

- Frequency response - 150 Hz - 7 kHz for handset, optional headset and hands-free speakerphone modes
- Codecs: G.711 (A-law and  $\mu$ -law), G.729AB, G.722, G.722.1, iLBC
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise generation
- DTMF tone generation (RFC 2833 and in-band)
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment

<sup>3</sup> Support for additional presence lines is available in a future release.

<sup>4</sup> Up to 50 users with an extension module

<sup>5</sup> To enjoy all the benefits of Polycom HD Voice when using the phone in the headset mode, you must use a wideband headset.

### Call Handling Features

- 12 lines (programmable line keys)
- Busy Lamp Field (BLF)
- Shared call/bridged line appearance
- Flexible line appearance (one or more line keys can be assigned for each line extension)
- Distinctive incoming call treatment/call waiting
- Call timer and call waiting
- Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- Local three-way audio conferencing
- One-touch speed dial, redial
- Remote missed call notification
- Do not disturb function
- Electronic hook switch capable
- Local configurable digit map/dial plan

### Other Features

- Adjustable base height

### Protocol Support

- IETF SIP (RFC 3261 and companion RFCs)

### Network and Provisioning

- SIP Protocol Support
- SDP
- IETF SIP (RFC 3261 and companion RFCs)
- Two-port Gigabit Ethernet switch
  - » 10/100/1000 Base-TX across LAN and PC ports
  - » Conforms to IEEE802.3-2005 (Clause 40) for Physical Media Attachment
  - » Conforms to IEEE802.3-2002 (Clause 28) for link Partner Auto-Negotiation
- Manual or dynamic host configuration protocol (DHCP) network setup

- Time and date synchronization using SNTP
- FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments
- Provisioning and call server redundancy supported
- QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP
- VLAN - CDP, DHCP VLAN discovery, LLDP-MED for VLAN discovery
  - » Network Address Translation (NAT) support for static configuration and “Keep-Alive” SIP signaling
- RTCP and RTP support
- Event logging
- Syslog
- Hardware diagnostics
- Status and statistics reporting
- IPv4
- TCP
- UDP
- DNS-SRV

### Power

- Built-in auto sensing IEEE 802.3 at Power over Ethernet (Class 2)
- External Universal AC Adaptor, 48VDC; 12W

### Approvals

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- VCCI Class B
- EN55024
- EN61000-3-2; EN61000-3-3
- NZ Telepermit
- UAE TRA
- Australia A & C Tick

### Safety

- UL 60950-1
- CE Mark
- CAN/CSA-C22.2 No. 60950-1
- EN 60950-1
- IEC 60950-1
- AS/NZS 60950-1
- ICASA (add)
- CITC (add)

### Operating Conditions

- Temperature: (+32 to 104°F (0 to 40°C))
- Relative Humidity: 5% to 95%, noncondensing

### Storage Temperature

- -40 to +160°F (-40 to +70°C)

### Package Contents

- VVX 410 console
- Handset with handset cord
- Network (LAN) cable – CAT-5E
- User guide
- Quick Tips reference card
- Ferrite clamp
- Power supply

### Size

- 7.5 x 6 x 7 in (19 x 15 x 18 cm) (WxHxD)

### Box Dimensions/Weight

- Unit weight: 2.0 lbs (0.9 kg)
- 12 x 8.25 x 4.25 in
- 3.1 lbs (1.4 kg)

### Country of Origin

- China